55500-00001_Z-Stop_20180321_1_55500_.pdf

ROLL REWIND DIRECTION

# Z-STOP®

**ZINC STRIP**
99.2% PURE ZINC

*INHIBITS ROOF MOSS, ALGAE AND FUNGUS FOR COMPOSITION OR SHAKE ROOFS*

Rain Releases Zinc-ions Inhibiting Growth

## 50' Roll

## Lasts 20+ Years

- Apply Z-STOP by butting it up against the ridge cap on both sides of all roof peaks. (see drawing at left) Apply Z-STOP below anything that blocks rain water flow, such as chimneys, gables and skylights. Rain water must run over Z-STOP to become effective.
- On roofs with moss, mildew, or fungus, the existing growth must first be removed, then the root systems must be chemically treated and destroyed. Install Z-STOP to keep it from growing back.
- Nail approximately every two feet with neoprene washered roofing nails.

*In areas of severe moss, mildew or fungus growth, several horizontal rows of Z-STOP application may be necessary to assure its effectiveness over the entire roof surface.*

Tools Required:
Hammer and Scissors. MIN. WT. 3 lbs.

0 28437 05050 4

ACTIVE INGREDIENTS

| | |
|---|---|
| Pure Zinc | 99.2% |
| Inert Ingredients | .8% |
| Total | 100.0% |

"CAUTION: SHARP EDGES"
"KEEP OUT OF REACH OF CHILDREN"

A Product of WESPAC
Lynnwood, WA 98037
(800) 845-5863
www.z-stop.com

MADE IN USA
SINCE 1984