PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

KEEP OUT OF REACH OF CHILDREN

Corrosive. Causes irreversible eye damage. Causes skin burns. May be fatal if swallowed or absorbed through skin. Harmful if inhaled. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Causes asthmatic signs and symptoms in hyper-reactive individuals.

Do not get in eyes, on skin, on clothing. Avoid breathing vapor. Do not swallow.

Wear goggles, protective clothing, and butyl or nitrile gloves.

Wash thoroughly with soap and water after handling.

Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

STORAGE AND HANDLING

NALCON 7637 is incompatible with many commonly used materials of construction such as steel, galvanized iron, aluminum, tin, and zinc. Nalcon 7637 can be stored and handled in baked phenolic-lined steel, polyethylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezes at about 7°F (-14°C). Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to 100°F (37.8°C) can be tolerated but the preferred maximum storage temperature is about 80°F (26.7°C).

A stainless steel centrifugal pump is suggested for transfer service. Spiral-wound stainless steel with $TEFLON^{\circledcirc}$ Polymer is suitable for gaskets and packing.

Handle in a well-ventilated area. If vapors are irritating to the nose or eyes, special ventilation or respiratory protection (MSHA/NIOSH approved air purifying respirator equipped with an organic vapor cartridge) may be required.

STORAGE AND DISPOSAL

PESTICIDE DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or your Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Triple or pressure rinse container (or equivalent) promptly after emptying. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or other procedures approved by state and local authorities.

BEFORE HANDLING OR USING THIS PRODUCT, SEE YOUR EMPLOYER AND READ THE CURRENT MATERIAL SAFETY DATA SHEET.



A HIGHLY EFFECTIVE MICROBIOCIDE FOR USE IN CONTROLLING BACTERIA INCLUDING SLIME FORMING BACTERIA AND SULFATE-REDUCING BACTERIA AND FUNGI (YEAST AND MOLDS) AND ALGAE IN PAPER MILLS AND PAPER MILL PROCESS WATER SYSTEMS AND WATER BASED COATINGS FOR PAPER AND PAPERBOARD.

Active Ingredient: Glutaraldehyde

ehyde 42.5%

Alkyl (C14 50%, C12 40%, C16 10%) dimethyl benzyl ammonium chloride 7.5%

Inert Ingredients

50.0% 100.0%

KEEP OUT OF REACH OF CHILDREN DANGER

FIRST AID

If swallowed:

- Call a poison control center or a doctor immediately for treatment advice.
- DO NOT INDUCE VOMITING.
- Do not give anything to drink.

If in eves:

- Wash immediately and continuously with flowing water for at least 30 minutes.
- Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical
 consultation, preferably from an ophthalmologist.
- · Call a poison control center or a doctor immediately for treatment advice.

If on skin or clothing:

- · Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- · Call a poison control center or a doctor immediately for treatment advice.

If inhaled:

- · Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, and then give artificial respiration, preferably
 mouth-to-mouth if possible.
- Call a poison control center or a doctor for further treatment advice.

NOTE TO PHYSICIAN: Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric lavage.

Have the MSDS and, if available, the product container or label with you when calling a poison control center or a doctor, or going for treatment.

IN CASE OF AN EMERGENCY endangering life or property involving this product, call (800) 424-9300.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA Reg. No. 464-702-1706

EPA Est. No. 1706-PA-1 (EL)

EPA Est. No. 1706-CN-1 (BU)

(Letters in () that match the prefix in batch number identify the establishment number.)

SOLD BY: Nalco Company 1601 West Diehl Road Naperville, IL 60563-1198

Made in USA

NET CONTENTS SHOWN ELSEWHERE ON CONTAINER



It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PAPER MILLS AND PAPER MILL PROCESS WATER SYSTEMS

NALCON 7637 should be added to a paper making system at a point of uniform mixing such as the thin or thick stock chest, save-all tank, process tank, or white-water tank.

Initial Dose: When the system is noticeably contaminated, add 0.5 to 3.0 lbs. of NALCON 7637 per ton or 0.15 to 1.5 Kg of NALCON 7637 per metric ton of pulp or paper (dry basis) as a continuous or slug dose. Repeat until control is achieved. Heavily fouled systems should be boiled out prior to initial treatment.

Subsequent Dose: When microbial control is evident, add 0.3 to 2.0 lbs. of NALCON 7637 per ton or 0.15 to 1.0 Kg of NALCON 7637 per metric ton of pulp or paper (dry basis) as necessary to maintain control.

WATER BASED COATINGS, PIGMENTS AND FILLER SLURRIES FOR PAPER AND PAPERBOARD


NOTE: For use in non-food contact coatings only.

Use from 0.1 to 0.6 lbs. of NALCON 7637 per 1,000 lbs. of dry powder to produce a concentration of 100 to 600 ppm as product (based on slurry solids) in the mixed slurry.

LIMITED WARRANTY AND DISCLAIMER

Seller warrants that the product conforms to its chemical description as contained on this label and is reasonably fit for the purposes stated on this label when used in accordance with directions under normal conditions of use. THE WARRANTIES MADE IN THIS PARAGRAPH ARE SELLER'S SOLE WARRANTIES WITH RESPECT TO THE PRODUCT AND ARE MADE EXPRESSLY IN LIEU OF AND EXCLUDE ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER EXPRESS OR IMPLIED REPRESENTATIONS AND WARRANTIES.





PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

KEEP OUT OF REACH OF CHILDREN

Corrosive. Causes irreversible eye damage. Causes skin burns. May be fatal if swallowed or absorbed through skin. Harmful if inhaled. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Causes asthmatic signs and symptoms in hyper-reactive individuals.

Do not get in eyes, on skin, on clothing.

Avoid breathing vapor. Do not swallow.

Wear goggles, protective clothing, and butyl or nitrile gloves.

Wash thoroughly with soap and water after handling.

Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

STORAGE AND HANDLING

NALCON 7637 is incompatible with many commonly used materials of construction such as steel, galvanized iron, aluminum, tin, and zinc. Nalcon 7637 can be stored and handled in baked phenolic-lined steel, polyethylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezes at about $7^{\circ}F$ (- $14^{\circ}C$). Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to $100^{\circ}F$ (37.8°C) can be tolerated but the preferred maximum storage temperature is about $80^{\circ}F$ (26.7°C).

A stainless steel centrifugal pump is suggested for transfer service. Spiral-wound stainless steel with $TEFLON^{@}$ Polymer is suitable for gaskets and packing.

Handle in a well-ventilated area. If vapors are irritating to the nose or eyes, special ventilation or respiratory protection (MSHA/NIOSH approved air purifying respirator equipped with an organic vapor cartridge) may be required.

STORAGE AND DISPOSAL

PESTICIDE DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or your Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Triple or pressure rinse container (or equivalent) promptly after emptying. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or other procedures approved by state and local authorities.

BEFORE HANDLING OR USING THIS PRODUCT, SEE YOUR EMPLOYER AND READ THE CURRENT MATERIAL SAFETY DATA SHEET.



A HIGHLY EFFECTIVE MICROBIOCIDE FOR USE IN CONTROLLING BACTERIA INCLUDING SLIME FORMING BACTERIA AND SULFATE-REDUCING BACTERIA AND FUNGI (YEAST AND MOLDS) AND ALGAE IN PAPER MILLS AND PAPER MILL PROCESS WATER SYSTEMS AND WATER BASED COATINGS FOR PAPER AND PAPERBOARD.

Active Ingredient: Glutaraldehyde

raldehyde 42.5% Alkyl (C14 50%, C12 40%, C16 10%)

dimethyl benzyl ammonium chloride

Inert Ingredients
Total

100.0% **DRFN**

50.0%

KEEP OUT OF REACH OF CHILDREN DANGER

FIRST AID

If swallowed:

- Call a poison control center or a doctor immediately for treatment advice.
- DO NOT INDUCE VOMITING.
- Do not give anything to drink.

If in eves:

- Wash immediately and continuously with flowing water for at least 30 minutes.
- Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical
 consultation, preferably from an ophthalmologist.
- Call a poison control center or a doctor immediately for treatment advice.

If on skin or clothing:

- · Take off contaminated clothing.
- · Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or a doctor immediately for treatment advice.

If inhaled:

- · Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, and then give artificial respiration, preferably
 mouth-to-mouth if possible.
- · Call a poison control center or a doctor for further treatment advice.

NOTE TO PHYSICIAN: Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric lavage.

Have the MSDS and, if available, the product container or label with you when calling a poison control center or a doctor, or going for treatment.

IN CASE OF AN EMERGENCY endangering life or property involving this product, call (800) 424-9300.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA Reg. No. 464-702-1706

EPA Est. No. 1706-PA-1 (EL)

EPA Est. No. 1706-CN-1 (BU)

(Letters in () that match the prefix in batch number identify the establishment number.)

SOLD BY: Nalco Company 1601 West Diehl Road Naperville, IL 60563-1198

Made in USA

NET CONTENTS SHOWN ELSEWHERE ON CONTAINER

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling

PAPER MILLS AND PAPER MILL PROCESS WATER SYSTEMS

NALCON 7637 should be added to a paper making system at a point of uniform mixing such as the thin or thick stock chest, save-all tank, process tank, or white-water tank.

Initial Dose: When the system is noticeably contaminated, add 0.5 to 3.0 lbs. of NALCON 7637 per ton or 0.15 to 1.5 Kg of NALCON 7637 per metric ton of pulp or paper (dry basis) as a continuous or slug dose. Repeat until control is achieved. Heavily fouled systems should be boiled out prior to initial treatment.

Subsequent Dose: When microbial control is evident, add 0.3 to 2.0 lbs. of NALCON 7637 per ton or 0.15 to 1.0 Kg of NALCON 7637 per metric ton of pulp or paper (dry basis) as necessary to maintain control.

WATER BASED COATINGS, PIGMENTS AND FILLER SLURRIES FOR PAPER AND PAPERBOARD


NOTE: For use in non-food contact coatings only.

Use from 0.1 to 0.6 lbs. of NALCON 7637 per 1,000 lbs. of dry powder to produce a concentration of 100 to 600 ppm as product (based on slurry solids) in the mixed slurry.

LIMITED WARRANTY AND DISCLAIMER

Seller warrants that the product conforms to its chemical description as contained on this label and is reasonably fit for the purposes stated on this label when used in accordance with directions under normal conditions of use. THE WARRANTIES MADE IN THIS PARAGRAPH ARE SELLER'S SOLE WARRANTIES WITH RESPECT TO THE PRODUCT AND ARE MADE EXPRESSLY IN LIEU OF AND EXCLUDE ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER EXPRESS OR IMPLIED REPRESENTATIONS AND WARRANTIES.





PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

KEEP OUT OF REACH OF CHILDREN

Corrosive. Causes irreversible eye damage. Causes skin burns. May be fatal if swallowed or absorbed through skin. Harmful if inhaled. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Causes asthmatic signs and symptoms in hyper-reactive individuals.

Do not get in eyes, on skin, on clothing. Avoid breathing vapor. Do not swallow.

Wear goggles, protective clothing, and butyl or nitrile gloves.

Wash thoroughly with soap and water after handling.

Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

STORAGE AND HANDLING

NALCON 7637 is incompatible with many commonly used materials of construction such as steel, galvanized iron, aluminum, tin, and zinc. Nalcon 7637 can be stored and handled in baked phenolic-lined steel, polyethylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezes at about $7^{\circ}F$ (- $14^{\circ}C$). Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to $100^{\circ}F$ (37.8°C) can be tolerated but the preferred maximum storage temperature is about $80^{\circ}F$ (26.7°C).

A stainless steel centrifugal pump is suggested for transfer service. Spiral-wound stainless steel with $TEFLON^{@}$ Polymer is suitable for gaskets and packing.

Handle in a well-ventilated area. If vapors are irritating to the nose or eyes, special ventilation or respiratory protection (MSHA/NIOSH approved air purifying respirator equipped with an organic vapor cartridge) may be required.

STORAGE AND DISPOSAL

PESTICIDE DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or your Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning of the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller. To clean container before final disposal, empty contents into application equipment and triple rinse. Pour or pump rinsate into application equipment or rinsate collection system. Then offer for recycling if available, or puncture and dispose of in a sanitary landfill, or by incineration, or by other procedures allowed by state and local authorities.

BEFORE HANDLING OR USING THIS PRODUCT, SEE YOUR EMPLOYER AND READ THE CURRENT MATERIAL SAFETY DATA SHEET.



A HIGHLY EFFECTIVE MICROBIOCIDE FOR USE IN CONTROLLING BACTERIA INCLUDING SLIME FORMING BACTERIA AND SULFATE-REDUCING BACTERIA AND FUNGI (YEAST AND MOLDS) AND ALGAE IN PAPER MILLS AND PAPER MILL PROCESS WATER SYSTEMS AND WATER BASED COATINGS FOR PAPER AND PAPERBOARD.

Active Ingredient: Glutaraldehyde

42.5%) 7.5%

Alkyl (C14 50%, C12 40%, C16 10%)

dimethyl benzyl ammonium chloride

Inert Ingredients
Total

50.0% 100.0%

KEEP OUT OF REACH OF CHILDREN DANGER

FIRST AID

If swallowed:

- Call a poison control center or a doctor immediately for treatment advice.
- DO NOT INDUCE VOMITING.
- · Do not give anything to drink.

If in eves:

- Wash immediately and continuously with flowing water for at least 30 minutes.
- Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical
 consultation, preferably from an ophthalmologist.
- Call a poison control center or a doctor immediately for treatment advice.

If on skin or clothing:

- · Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or a doctor immediately for treatment advice.

If inhaled:

- · Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, and then give artificial respiration, preferably
 mouth-to-mouth if possible.
- · Call a poison control center or a doctor for further treatment advice.

NOTE TO PHYSICIAN: Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric lavage.

Have the MSDS and, if available, the product container or label with you when calling a poison control center or a doctor, or going for treatment.

IN CASE OF AN EMERGENCY endangering life or property involving this product, call (800) 424-9300.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

EPA Reg. No. 464-702-1706

EPA Est. No. 1706-PA-1 (EL) EPA Est. No. 1706-CN-1 (BU)

(Letters in () that match the prefix in batch number identify the establishment number.)

SOLD BY: Nalco Company 1601 West Diehl Road Naperville, IL 60563-1198

Made in USA

NET CONTENTS SHOWN ELSEWHERE ON CONTAINER

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PAPER MILLS AND PAPER MILL PROCESS WATER SYSTEMS

NALCON 7637 should be added to a paper making system at a point of uniform mixing such as the thin or thick stock chest, save-all tank, process tank, or white-water tank.

Initial Dose: When the system is noticeably contaminated, add 0.5 to 3.0 lbs. of NALCON 7637 per ton or 0.15 to 1.5 Kg of NALCON 7637 per metric ton of pulp or paper (dry basis) as a continuous or slug dose. Repeat until control is achieved. Heavily fouled systems should be boiled out prior to initial treatment.

Subsequent Dose: When microbial control is evident, add 0.3 to 2.0 lbs. of NALCON 7637 per ton or 0.15 to 1.0 Kg of NALCON 7637 per metric ton of pulp or paper (dry basis) as necessary to maintain control.

WATER BASED COATINGS, PIGMENTS AND FILLER SLURRIES FOR PAPER AND PAPERBOARD

NOTE: For use in non-food contact coatings only.

Use from 0.1 to 0.6 lbs. of NALCON 7637 per 1,000 lbs. of dry powder to produce a concentration of 100 to 600 ppm as product (based on slurry solids) in the mixed slurry.

LIMITED WARRANTY AND DISCLAIMER

Seller warrants that the product conforms to its chemical description as contained on this label and is reasonably fit for the purposes stated on this label when used in accordance with directions under normal conditions of use. THE WARRANTIES MADE IN THIS PARAGRAPH ARE SELLER'S SOLE WARRANTIES WITH RESPECT TO THE PRODUCT AND ARE MADE EXPRESSLY IN LIEU OF AND EXCLUDE ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER EXPRESS OR IMPLIED REPRESENTATIONS AND WARRANTIES.



