

Coverage

Estimate 150 to 300 sq. ft. per gallon for brush coat or 5 to 10 gallons per 1000 board feet for dipping dimensional lumber.

Recommended for

COPPER GREEN® Brown Wood Preservative is an easy to use wood preservative for above ground, ground contact and below ground contact and below ground uses: e.g. lumber, poles and pole tops, greenhouse benches, foundations, sills, planter boxes, fence posts, lawn furniture, decks, and remedial treatment of treated wood. For use wherever wood meets soil or water. Must not be applied to food or feed contact surfaces.

THIS WILL TURN WOOD BROWN. Use wherever wood meets water or soil. Seals wood - kills termites & wood-eating insects. Prevents deterioration caused by: Termites, Rot & Decay, Fungus & Mold (Previene la deterioración causada por: Termitas, Putrefacción y Decaimiento, Hongo y Molo). Full Strength - No thinning - No Diluting.

FOR EXTERIOR USE ONLY. Application of this product may produce a strong, lingering, unpleasant odor. Wood to be protected against subterranean termites must be treated before use in construction. Termites will not attack wood treated with COPPER GREEN® Brown Wood Preservative.

Directions for Use: It is a violation of federal law to use this product in a manner inconsistent with its labeling.

Wood to be treated must be dry and well seasoned before treatment with COPPER GREEN® Brown Wood Preservative. Lumber and wood products must be dip treated for at least 3 minutes per inch thickness. If dipping is not possible, treat with several flowing coats by brush. The more COPPER GREEN® Brown Wood Preservative the wood absorbs, the better it will be protected. Do not try to extend the coverage.

Fence posts and heavy timbers must be free from bark, dry and well seasoned and must be immersed in COPPER GREEN® Brown Wood Preservative for 12-48 hours to give effective control for wood destroying pests.

Apply prior to use in construction. Ends or edges cut or bored after initial treatment must be brushed with COPPER GREEN® Brown Wood Preservative. Do not install treated articles until thoroughly dry.

Use one coat on materials to be finished with paint. If no finish is to be used, apply two liberal coats within the hour. Thoroughly cover the ends. The more preservative absorbed into the wood, the longer and more effective the protection.

The copper fungicide gives a brown cast to COPPER GREEN® Brown Wood Preservative. This product will tint wood but is not intended for use as a stain. The brown color will fade within a few months when exposed to sunlight. Oil or Alkyd stains or paints can be applied over COPPER GREEN® Brown Wood Preservative after thorough drying (about 48 hours), but the brown may bleed through lighter colors. Do not overcoat with latex paint until thoroughly cured (6 to 12 months).

The application rate for wood treated with copper naphthenate in a diptank shall not exceed 25%.

This product is supplied at proper application consistency and is to be applied without thinning or diluting under normal environmental and application conditions. Brushes and other application equipment may be cleaned with paint thinner (mineral spirits). Do not apply with an airless sprayer.

GREEN PRODUCTS CO.

810 Market Avenue • Richmond, CA 94801-1325

(510) 235-9667

EPA Establishment No. 66591-CA-01

EPA REG. NO. 66591-1

greenproductsco.net

NOTICE: Green Products Co. liability under any expressed or implied warranty is limited solely to replacement of Green Products Co. products proved defective and does NOT include labor or other consequential damages. We assume no liability for damages. The suitability of the product for any intended use is solely up to the user.



COPPER-GREEN® BROWN WOOD PRESERVATIVE (PRESERVANTE PARA MADERA)

Use wherever
wood meets
water or soil.
Seals wood.
Kills termites
& wood eating
insects.

Pressure-Treated
wood can
be treated
immediately.

WARNING A V I S O

Keep out of Reach of Children.
(Mantenga fuera del alcance de los niños)

See Side Panel for Additional Precautionary Statements.

ACTIVE INGREDIENT:

Copper Naphthenate (CAS # 1338-02-9) 10.0%

OTHER INGREDIENTS: 90.0%

Total 100.0%

*Equivalent to 1.18% metallic copper

COMBUSTIBLE: Contains Petroleum Distillates

Max V.O.C. = 350 grams per liter

CONTENTS UNDER PRESSURE: Do not incinerate,
puncture or store above 140°F (57°C) or below 15°F (-9°C).

NET WT. 14 FL. OZ. (413mL)

Precautionary Statements Hazards to humans and domestic animals

WARNING: Harmful if swallowed, absorbed through skin or inhaled. Causes eye and skin irritation. Do not get in eyes, on skin or on clothing. Prolonged or repeated skin contact may cause allergic reaction in some individuals.

PERSONAL PROTECTIVE EQUIPMENT: Applicators must wear chemical resistant gloves while handling or applying naphthenate salts. Do not breath vapor. Wear a mask or pesticide respirator jointly approved by the Mine Safety and Health Administration and the National Institute for Occupational Safety and Health. Wash thoroughly with soap and water after handling and before eating. Remove contaminated clothing and wash clothing before reuse. Blender operators must wear organic vapor respirators while applying naphthenate salts to non-pressure treated wood. Clean-up crew occupational handlers applying dip diffusion treatment must wear a minimum of a NIOSH approved (TC-84A) air-purifying half-mask elastomeric respirator with any R or P filter.

FIRST AID	
IF IN EYES:	- Hold eye open and rinse slowly and gently with water for 15-20 minutes. - Remove contact lenses, if present, after the first 5 minutes, then continue rinsing. - Call a Poison Control Center or doctor for treatment advice.
IF ON SKIN OR CLOTHING:	- Take off contaminated clothing. - Rinse skin immediately with plenty of water for 15-20 minutes. - Call a Poison Control Center or doctor for treatment advice.
IF SWALLOWED:	- Call a Poison Control Center or doctor immediately for treatment advice. - Do not induce vomiting unless told to do so by a Poison Control Center or doctor. - Do not give any liquid to the person. - Do not give anything by mouth to an unconscious person.
IF INHALED:	- Move person to fresh air. - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferable mouth-to-mouth if possible. - Call a Poison Control Center or doctor immediately for treatment advice.
Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. In case of medical questions, emergencies or accidents involving this product call INFOTRAC at (800) 535-5053	
NOTE TO PHYSICIAN Contains petroleum distillates - vomiting may cause aspiration pneumonia.	

Environmental Hazards

This product is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a national Pollution Discharge Elimination System (NPDES) permit and permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Wood treated with Copper-Green® Wood Preservative shall not be used in the construction of beehives.

Physical or Chemical Hazards

Do not use, pour, spill or store near heat or open flame. Use only with adequate ventilation. Close container when not in use.

Storage and Disposal

Storage: Store in a secure, well ventilated area, protected from extreme temperatures. If the product has been spilled or is leaking, remove the source of the spill or leak. Recover free liquid. Spread absorbent, then pick up and place in containers. Then, where applicable, wash area with detergent and water. Store product in the original container only. Do not contaminate water, food or feed by storage or disposal. Keep container closed when not in use.

Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticides or rinsate is a violation of federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

Container Disposal: Nonrefillable container. Do not reuse or refill this container. Offer for recycling, if available, or puncture and dispose of in a sanitary landfill, or incineration. Do not burn, unless allowed by state and local ordinances. If burned, stay out of smoke.

**No thinning or diluting. Use Full strength.
This Product Will Turn Wood Brown**

Coverage
Estimate 150 to 300 sq. ft. per gallon for brush coat or 5 to 10 gallons per 1000 board feet for dipping dimensional lumber.

Recommended for
COPPER-GREEN® Brown Wood Preservative is an easy to use wood preservative for above ground, ground contact and below ground contact and below ground uses: e.g. lumber, poles and pole tops, , greenhouse benches, foundations, sills, planter boxes, fence posts, lawn furniture, decks and remedial treatment of treated wood. . For use wherever wood meets soil or water. Must not be applied to food or feed contact surfaces.

THIS WILL TURN WOOD BROWN. Use wherever wood meets water or soil. Seals wood - kills termites & wood-eating insects. Prevents deterioration caused by: Termites, Rot & Decay, Fungus & Mold (Previene la deterioración causada por: Termitas, Putrefacción y Decaimiento, Hongo y Molo). Full Strength - No Thinning - No Diluting.

FOR EXTERIOR USE ONLY. Application of this product may produce a strong, lingering, unpleasant odor. Wood to be protected against subterranean termites must be treated before use in construction. Termites will not attack wood treated with COPPER-GREEN® Brown Wood Preservative.

Directions for Use:
It is a violation of federal law to use this product in a manner inconsistent with its labeling.
Wood to be treated must be dry and well seasoned before treatment with COPPER-GREEN® Brown Wood Preservative. Lumber and wood products must be dip treated for at least 3 minutes per inch thickness. If dipping is not possible, treat with several flowing coats by brush. The more COPPER-GREEN® Brown Wood Preservative the wood absorbs, the better it will be protected. Do not try to extend the coverage.
Fence posts and heavy timbers must be free from bark, dry and well seasoned and must be immersed in COPPER-GREEN® Wood Preservative for 12-48 hours to give effective control for wood destroying pests. Apply prior to use in construction. Ends or edges cut or bored after initial treatment must be brushed with COPPER-GREEN® Brown Wood Preservative. Do not install treated articles until thoroughly dry.
Use one coat on materials to be finished with paint or stain. If no finish is to be used, apply two liberal coats within the hour. Thoroughly cover the ends. The more preservative absorbed into the wood, the longer and more effective the protection.
The copper fungicide gives a brown cast to COPPER-GREEN® Brown Wood Preservative. This product will tint wood but is not intended for use as a stain. The green color will fade within a few months when exposed to sunlight. Oil or Alkyd stains or paints can be applied over COPPER-GREEN® Brown Wood Preservative after thorough drying (about 48 hours), but the green may bleed through lighter colors. Do not overcoat with latex paint until thoroughly cured (6 to 12 months).
The application rate for wood treated with copper naphthenate in a diptank shall not exceed 25%.
This product is supplied at proper application consistency and is to be applied without thinning or diluting under normal environmental and application conditions. Brushes and other application equipment may be cleaned with paint thinner (mineral spirits). Do not apply with an airless sprayer.

COPPER-GREEN® BROWN WOOD PRESERVATIVE

(PRESERVANTE PARA MADERA)



Use wherever wood meets water or soil. Seals wood. Kill termites & wood eating insects.

Pressure-Treated wood can be treated immediately.

WARNING AVISO

Keep out of Reach of Children.
(Mantiene fuera del alanche de niños)

Contents 1 Gallon (128 fl. oz.) 3.79 Liter

See Side Panel for Additional Precautionary Statements.
ACTIVE INGREDIENT:
Copper Naphthenate (CAS # 1338-02-9) 10.0%
OTHER INGREDIENTS 90.0%
Total 100.0%
*Equivalent to 1.18% metallic copper
COMBUSTIBLE: Contains Petroleum Distillates
V.O.C. = 342 grams per liter

Precautionary Statements Hazards to humans and domestic animals

WARNING: Harmful if swallowed, absorbed through skin or inhaled. Causes eye and skin irritation. Do not get in eyes, on skin or on clothing. Prolonged or repeated skin contact may cause allergic reaction in some individuals.

PERSONAL PROTECTIVE EQUIPMENT
Applicators must wear chemical resistant gloves while handling or applying naphthenate salts. Do not breathe vapor. Wear a mask or pesticide respirator jointly approved by the Mine Safety and Health Administration and the National Institute for Occupational Safety and Health. Wash thoroughly with soap and water after handling and before eating. Remove contaminated clothing and wash clothing before reuse. Blender operators must wear organic vapor respirators while applying naphthenate salts to non-pressure treated wood. Clean-up crew occupational handlers applying dip diffusion treatment must wear a minimum of a NIOSH approved (TC-84A) air-purifying half-mask elastomeric respirator with any R or P filter.

ENVIRONMENTAL HAZARDS
This product is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Wood treated with COPPER-GREEN® Brown Wood Preservative shall not be used in the construction of beehives.

PHYSICAL OR CHEMICAL HAZARDS
Combustible. Do not use, pour or spill, or store near heat or open flame. Use only with adequate ventilation. Close container when not in use

Storage and Disposal
Storage: Store in a secure, well ventilated area, protected from extreme temperatures. If the product has been spilled or is leaking, remove the source of the spill or leak. Recover free liquid. Spread absorbent, then pick up and place in containers. Then, where applicable, wash area with detergent and water. Store product in the original container only. Do not contaminate water, food or feed by storage or disposal. Keep container closed when not in use.

This Product Will Turn Wood Brown
NOTICE: Green Products Co. liability under any expressed or implied warranty is limited solely to replacement of Green Products Co. products proved defective and does NOT include labor or other consequential damages. We assume no liability for damages. The suitability of the product for any intended use is solely up to the user.
No thinning or diluting. Use Full strength.

Declaración de Medidas Preventivas
Peligros a humanos y animals domésticos
PRECAUCION: DAÑINO O MORTAL SI SE INHIERE
Causa irritación a los ojos y la piel. Dañino si se absorbe pro la poiel. No respire vapores o rocío durante la aplicación con brocha, rodillo, roceador o al sumergi. No salpique en los ojos, le piel o en la ropa. Cuando rocía este producto continuamente o en uso prolongo o para el eso frecuente de seste producto, póngase un repirador para roceador vapor aprobado por NIO-SHIMNSA. Lave meticulosamente con agua y jabón desputés de usar. Quites la vestimenta contaminada. Lávela completamente antes de volvería a usar. Use en área ventilada.

Declaración de Tratamiento Práctico
- Si en los ojos Inmediatamente enjuage can mucha agua y busque a atención médica.
- Si en la piel Lave completamente con mucho jabón e agua. Busque atención médica si la irritación persiste.
- Si se inhala Lieve a la victima al aire fresco. Si no respira aplique respiración artificial, preferiblemente boco-a-boca. Busque atención médica
- Si se inhieri No induzca vómitos. LLAME A UN MÉDICO IMMEDATAMENTE.

	First Aid
IF IN EYES:	• Hold eye open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. • Call a poison control center or doctor for treatment advice.
IF ON SKIN OR CLOTHING:	• Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15-20 minutes. • Call a Poison Control Center or doctor for treatment advice.
IF SWALLOWED:	• Call a Poison Control Center or doctor immediately for treatment advice. • Do not induce vomiting unless told to do so by a poison control center or doctor. • Do not give any liquid to the person. • Do not give anything by mouth to an unconscious person.
IF INHALED:	• Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. • Call a poison control center or doctor for further treatment advice.
Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. In case of medical questions, emergencies or accidents involving this product call INFOTRAC at (800) 535-5053.	
NOTE TO PHYSICIAN Contains petroleum distillates - vomiting may cause aspiration pneumonia.	

GREEN PRODUCTS CO.
810 Market Avenue • Richmond, CA 94801-1325
(510) 235-9667
www.greenproductsco.net
EPA Establishment No. 66591 CA 01
EPA REG. NO.66591-1



Coverage
Estimate 150 to 300 sq. ft. per gallon for brush coat or 5 to 10 gallons per 1000 board feet for dipping dimensional lumber.

Recommended for
COPPER-GREEN® Brown Wood Preservative is an easy to use wood preservative for above ground, ground contact and below ground contact and below ground uses: e.g. lumber, poles and pole tops, greenhouse benches, foundations, sills, planter boxes, fence posts, lawn furniture, decks and remedial treatment of treated wood. For use wherever wood meets soil or water. Must not be applied to food or feed contact surfaces.

THIS WILL TURN WOOD BROWN. Use wherever wood meets water or soil. Seals wood - kills termites & wood-eating insects. Prevents deterioration caused by: Termites, Rot & Decay, Fungus & Mold (Previene la deterioración causada por: Termitas, Pudrefacción y Decaimiento, Hongo y Moho). Full Strength - No Thinning - No Diluting.

FOR EXTERIOR USE ONLY. Application of this product may produce a strong, lingering, unpleasant odor. Wood to be protected against subterranean termites must be treated before use in construction. Termites will not attack wood treated with COPPER-GREEN® Brown Wood Preservative.

Directions for Use:
It is a violation of federal law to use this product in a manner inconsistent with its labeling.
Wood to be treated must be dry and well seasoned before treatment with COPPER-GREEN® Brown Wood Preservative. Lumber and wood products must be dip treated for at least 3 minutes per inch thickness. If dipping is not possible, treat with several flowing coats by brush. The more COPPER-GREEN® Brown Wood Preservative the wood absorbs, the better it will be protected. Do not try to extend the coverage.
Fence posts and heavy timbers must be free from bark, dry and well seasoned and must be immersed in COPPER-GREEN® Wood Preservative for 12-48 hours to give effective control for wood destroying pests.
Apply prior to use in construction. Ends or edges cut or bored after initial treatment must be brushed with COPPER-GREEN® Wood Preservative.
Do not install treated articles until thoroughly dry.
Use one coat on materials to be finished with paint or stain. If no finish is to be used, apply two liberal coats within the hour. Thoroughly cover the ends. The more preservative absorbed into the wood, the longer and more effective the protection.
The copper fungicide gives a brown cast to COPPER-GREEN® Brown Wood Preservative. This product will tint wood but is not intended for use as a stain. The green color will fade within a few months when exposed to sunlight. Oil or Alkyd stains or paints can be applied over COPPER-GREEN® Brown Wood Preservative after thorough drying (about 48 hours), but the green may bleed through lighter colors. Do not overcoat with latex paint until thoroughly cured (6 to 12 months).
The application rate for wood treated with copper naphthenate in a dip tank shall not exceed 25%.
This product is supplied at proper application consistency and is to be applied without thinning or diluting under normal environmental and application conditions. Brushes and other application equipment may be cleaned with paint thinner (mineral spirits). Do not apply with an airless sprayer.

COPPER-GREEN® BROWN WOOD PRESERVATIVE (PRESERVANTE PARA MADERA)



Use wherever wood meets water or soil. Seals wood. Kill termites & wood eating insects.

Pressure-Treated wood can be treated immediately.

WARNING AVISO

Keep out of Reach of Children.
(Mantenga fuera del alcance de los niños)

See Side Panel for Additional Precautionary Statements.

ACTIVE INGREDIENT:
Copper Naphthenate (CAS # 1338-02-9) 10.0%
OTHER INGREDIENTS 90.0%
Total 100.0%

*Equivalent to 1.18% metallic copper
COMBUSTIBLE: Contains Petroleum Distillates
U.O.C. = 342 grams per liter

NET CONTENTS 1 QT. (32 fl. oz.)

Precautionary Statements Hazards to humans and domestic animals

WARNING: Harmful if swallowed, absorbed through skin or inhaled. Causes eye and skin irritation. Do not get in eyes, on skin or on clothing. Prolonged or repeated skin contact may cause allergic reaction in some individuals.

PERSONAL PROTECTIVE EQUIPMENT:
Applicators must wear chemical resistant gloves while handling or applying naphthenate salts. Do not breathe vapor. Wear a mask or pesticide respirator jointly approved by the MHA Safety and Health Administration and the National Institute for Occupational Safety and Health. Wash thoroughly with soap and water after handling and before eating. Remove contaminated clothing and wash clothing before reuse. Blender operators must wear organic vapor respirators while applying naphthenate salts to non-pressure treated wood. Clean-up crew occupational handlers applying dip diffusion treatment must wear a minimum of a NIOSH approved (TC-84A) air-purifying half-mask elastomeric respirator with any R or P filter.

First Aid	
IF IN EYES:	• Hold eye open and rise slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. • Call a poison control center or doctor for treatment advice.
IF ON SKIN OR CLOTHING:	• Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15-20 minutes. • Call a Poison Control Center or doctor for treatment advice.
IF SWALLOWED:	• Call a Poison Control Center or doctor immediately for treatment advice. • Do not induce vomiting unless told to do so by a poison control center or doctor. • Do not give any liquid to the person. • Do not give anything by mouth to an unconscious person.
IF INHALED:	• Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. • Call a poison control center or doctor for further treatment advice.
Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. In case of medical questions, emergencies or accidents involving this product call INFOTRAC at (800) 535-5053.	
NOTE TO PHYSICIAN Contains petroleum distillates - vomiting may cause aspiration pneumonia.	

Environmental Hazards
This product is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Wood treated with COPPER-GREEN® Brown Wood Preservative shall not be used in the construction of beehives.

Physical or Chemical Hazards
Combustible. Do not use, pour or spill, or store near heat or open flame. Use only with adequate ventilation. Close container when not in use.

Storage and Disposal
Storage: Store in a secure, well ventilated area, protected from extreme temperatures. If the product has been spilled or is leaking, remove the source of the spill or leak. Recover free liquid. Spread absorbent, then pick up and place in containers. Then, where applicable, wash area with detergent and water. Store product in the original container only. Do not contaminate water, food or feed by storage or disposal. Keep container closed when not in use.

Pesticide Disposal: Pesticide wastes are toxic. Improper disposal of excess pesticides, mixture, or rinsate is a violation of federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

Container Handling: Nonrefillable container. Do not reuse or refill this container. Offer for recycling, if available, or puncture and dispose of in a sanitary landfill, or incineration. Do not burn, unless allowed by state and local ordinances. If burned, stay out of smoke.

This Product Will Turn Wood Brown

NOTICE: Green Products Co. liability under any expressed or implied warranty is limited solely to replacement of Green Products Co. products proved defective and does NOT include labor or other consequential damages. We assume no liability for damages. The suitability of the product for any intended use is solely up to the user.

Declaración de Medidas Preventivas Peligros a humanos y animals domésticos
PRECAUCION: DAÑO O MORTAL SI SE INHIERE
Causa irritación a los ojos y la piel. Dañino si se absorbe por la piel. No respire vapores o rocío durante la aplicación con brocha, rodillo, roceador o al sumergir. No salpique en los ojos, le piel o en la ropa. Cuando rocía este producto continuamente o en uso prolongado o para el uso frecuente de seste producto, póngase un respirador para roceador vapor aprobado por NIO-SHIMNSA. Lave metuculosamente con agua y jabón después de usar. Quite las vestimenta contaminada. Lávela completamente antes de volvería a usar. Use en área ventilada.

Declaración de Tratamiento Práctico
- Si en los ojos Inmediatamente enjuague con mucha agua y busque a atención medica.
- Si en la piel Lave completamente con mucho jabón e agua. Busque atención médica si la irritación persiste.
- Si se inhala Lieve a la víctima al aire fresco. Si no respira aplique respiración artificial, preferiblemente boco-a-boca. Busque atención médica.
- Si se inhiera No induzca vómitos. LLAME A UN MÉDICO INMEDIATAMENTE.

No thinning or diluting. Use Full strength.

GREEN PRODUCTS CO.
810 Market Avenue
Richmond, CA 94801-1325
(510) 235-9667
www.greenproductscs.net

EPA Establishment No. 66591 CA 01
EPA REG. NO.66591-1

