

 West Marine®

**CPP®**

**Ablative Antifouling Paint**

**COMPOSITE  
COPPER TECHNOLOGY**

**BLUE**

Model 12845723

**NET CONTENTS: One U.S. Quart (946 mL)**

KEEP OUT OF REACH OF CHILDREN

**WARNING**

**COMBUSTIBLE LIQUID AND VAPOR. VAPOR HARMFUL. FATAL IF SWALLOWED.  
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.**

**ACTIVE INGREDIENT:**

Cuprous Oxide\* 23.7%

**INERT INGREDIENTS** 76.3%

**TOTAL** 100.0%

\*Metallic copper equivalent 21.05%

Contains petroleum distillates, xylene or xylene range aromatic solvents.



DISCLAIMER: The performance of any marine paint or coating depends on many factors outside the control of Pettit Paint Company, including surface preparation, proper application and environmental conditions. Therefore, Pettit Paint Company cannot guarantee this product's suitability for your particular purpose of application. Implied warranties of fitness for a particular purpose and of merchantability are excluded. Pettit Paint Company shall not under any circumstances be liable for incidental or consequential damages. By purchase or use of this product, buyer agrees that the sole and exclusive remedy, if any, is limited to the refund of the purchase price or replacement of the product at Pettit Paint's option.



EPA EST. NO. 60061-NU-2  
EPA REGISTRATION NO. 60061-132

KOP-COAT, INC.  
36 PAUL STREET  
HUCKAWAY, NJ 07736

50-616 10/27/14

PHX#1314705 02/26/15



|                             |               |
|-----------------------------|---------------|
| <b>ACTIVE INGREDIENT:</b>   |               |
| Cuprous Oxide*              | 23.7%         |
| <b>INERT INGREDIENTS</b>    | <b>76.3%</b>  |
| <b>TOTAL</b>                | <b>100.0%</b> |
| *Metallic copper equivalent | 21.05%        |

Contains petroleum distillates, xylene or xylene range aromatic solvents.

EPA EST. NO. 60061-NJ-2  
EPA REGISTRATION NO. 60061-122

KOP-COAT, INC.  
26 PINE STREET  
ROCKAWAY, NJ 07866

**DIRECTIONS FOR USE**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.  
**Product Description:** This product uses the latest developments in copper technology. Composite cuprous oxide contains the same level of copper by volume as traditional cuprous oxide but at a much lower weight and therefore less copper by weight is needed to provide maximum protection from fouling of all kinds. Low density copper guards against attachment of barnacles, anemones, hydroids, bryozoa, hydroids, algae and other fouling organisms. This product applies easily and dries quickly. It may be used over old antifouling finishes in good condition. This product is ideal for fiberglass, wood and properly primed steel boats.  
**Compatibility:** This product may be applied over most aged hard and soft antifouling coatings. Old tin copolymers and Teflon finishes must be completely removed before applying this product.  
**Mixing:** It is necessary to thoroughly mix the paint before using. If possible shake the can of paint on a mechanical paint shaker. Before using check the sides and bottom of the can to make sure all the pigment has been mixed in. If mixing is going to be done with a wooden paddle or an electric drill mixer, pour off half of the liquid from the top of the can into another can and then properly mix in any settled pigment, then mix the two parts together thoroughly.  
**Application Temperature:** 40°F to 90°F.  
**Application Method:** Brush, roller, airless or conventional spray.  
**Thinning:** Thinning this product is not normally required. If thinning is necessary, use Pettit 120 Brushing Thinner for a smoother finish on especially warm and breezy days. Use Pettit 121 Spraying Thinner for spray application. Do not thin more than 10% by volume (12 ounces per gallon), or inadequate paint film thickness may result in premature erosion of the finish. Use any of the above thinners for clean-up.  
**Coverage:** 500 square feet per gallon.  
**Number of Coats:** Two or three coats should be applied for best antifouling protection. Do not apply this product if rain or dew is expected before the surface has dried completely.  
**Dry Times:**

|      |                  |                  |
|------|------------------|------------------|
|      | <b>To recoat</b> | <b>To launch</b> |
| 50°F | 2 hours          | 2 hours          |
| 70°F | 3 hours          | 4 hours          |
| 80°F | 6 hours          | 8 hours          |

The above dry times are minimums. This product may be recoated and launched after the minimum times shown. There is no maximum dry time before launching.  
**VOC:** Less than 520 grams/liter (2.67 lbs/gallon) as specified.  
**Maintenance of Antifouling Paint:** No antifouling paint can be effective under all conditions of exposure. Max-made pollution and natural occurrences can adversely affect antifouling paint performance. Extreme hot and cold water temperatures, pH, dirt, oil, brackish water and even electrolysis can ruin a performing paint. Therefore, we strongly suggest that the bottom of the boat be checked regularly to make sure it is clean and that no growth is occurring. The self-cleaning nature of the coating is most effective when the boat is used periodically. Boats and vessels should not be scrubbed or cleaned for the first six months in the water and at intervals of not less than 3 months thereafter.

**SYSTEMS:** Mix paint thoroughly to ensure toxicants are evenly dispersed throughout the can. All surfaces must be clean, dry and properly prepared prior to painting.

**Previously Painted Surfaces:** If the previous coating is in good condition thoroughly sand with 80 grit paper then solvent clean with Pettit 120 Brushing Thinner to remove sanding residue. Apply two coats of this product observing the proper dry times. If the previous coating is soft or in poor condition, remove to the bare surface by sanding or using paint and varnish remover. Proceed with the appropriate bare system as described below. Old tin copolymer paints must be removed or may be sealed with Pettit 6527 Tie-Coat Primer before applying this product.

**Bare Fiberglass:** All bare fiberglass, regardless of age, must be thoroughly cleaned and de-waxed with Pettit 92 Bio-Blue Hull Surface Prep or de-waxed several times with Pettit 095 De-waxer. Sand thoroughly with 80 grit sandpaper to a dull, frosty finish and rewash the sanded surface with 120 Brushing Thinner to remove sanding residue. Then apply two coats of this product, following application instructions.

To eliminate the sanding operation, two methods are available:

1. Clean and de-wax the surface as described above, apply one very thin coat of 6998 Skip-Sand Primer using 3/16" or less nap roller or brush apply. Consult the primer label for complete application and antifouling top-coating instructions. Then apply two coats of this product or
2. Clean, de-wax and etch the surface with 92 Bio-Blue Hull Surface Prep using a coarse Scotchbrite® pad in a swirling motion. Clean off all residue by rinsing or wiping off with fresh water. Apply one coat of Pettit Protect Epoxy Primer. Consult the primer label for complete application and antifouling top-coating instructions. Then apply two coats of this product.

**Bare Wood:** Sand the entire surface with 80 grit paper and wipe clean with a rag dampened with 120 Brushing Thinner. Apply a coat of this product thinned 25% with 120 Brushing Thinner to penetrate and seal the wood. Fill any open seams with Pettit Seam Compound and allow to dry overnight. Apply two full coats of this product observing the proper dry times.

**Steel Hulls, Underwater Metal Parts and Keels:** For steel hulls and metal keels, consult Pettit Technical Bulletin TB431 High Bu'd Epoxy Primer for complete priming instructions or consult the Pettit Technical Department or your local Pettit representative. For underwater metal parts, consult Technical Bulletin TB112 Underwater Running Gear Painting Specification for complete priming and application details.

**All Other Substrates:** Please go to [www.pettit.com](http://www.pettit.com) and consult the product data sheet.

**DO NOT USE THIS PRODUCT ON ALUMINUM HULLS OR OUTDRIVES**

**Warning:** We guarantee this material to comply with our published specifications. Since the use of this material is beyond our control, we disclaim responsibility for its handling, use, storage, the results obtained or any injury or damage of any nature resulting thereon.

**MEDICAL EMERGENCIES:** 1-800-548-8488  
**PRODUCT INFORMATION:** 1-800-221-4466 or [WWW.PETTIT.PAINT.COM](http://WWW.PETTIT.PAINT.COM)

**PRECAUTIONARY STATEMENTS**

**HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**WARNING:** Causes eye irritation. Harmful if absorbed through skin. Avoid contact with skin, eyes or clothing. Fatal if swallowed. Do not breathe vapors, spray mist or sanding dust. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet.

**Personal Protective Equipment (PPE):** Mixers, loaders, applicators and other handlers must wear the following: Protective eyewear, chemical resistant gloves such as Nitrile Rubber Gloves greater than 14 mils thick, long sleeved shirt, long pants, and shoes plus socks. While restoring existing paint by sanding or blasting, or applying new antifouling paint, commercial users must wear a respirator with an organic-vapor removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval number prefix TC-252), or a cartridge approved for pesticides (MSHA/NIOSH approval number prefix TC-143) or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any N, R, P or HE prefilter. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Discard clothing and other absorbent material that have been drenched or heavily contaminated with the product's concentrate. Do not reuse them.

**USER SAFETY RECOMMENDATIONS**

Users should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. Users should remove clothing/PPE immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling this product. As soon as possible, wash thoroughly and change into clean clothing. Wash the outside of gloves before removing.

**FIRST AID**

|                                |   |
|--------------------------------|---|
| <b>IF SWALLOWED:</b>           | <ul style="list-style-type: none"> <li>• Call a poison control center or doctor immediately for treatment advice.</li> <li>• Do not give any liquid to the person.</li> <li>• Do not induce vomiting unless told to do so by a poison control center or doctor.</li> <li>• Do not give anything by mouth to an unconscious person.</li> </ul> |
| <b>IF IN EYES:</b>             | <ul style="list-style-type: none"> <li>• Hold eye open and rinse slowly and gently with water for 15-20 minutes.</li> <li>• Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.</li> <li>• Call a poison control center or doctor for treatment advice.</li> </ul>                                       |
| <b>IF ON SKIN OR CLOTHING:</b> | <ul style="list-style-type: none"> <li>• Take off contaminated clothing.</li> <li>• Rinse skin immediately with plenty of water for 15-20 minutes.</li> <li>• Call a poison control center or doctor for treatment advice.</li> </ul>   |
| <b>IF INHALED:</b>             | <ul style="list-style-type: none"> <li>• Move person to fresh air.</li> <li>• If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth, if possible.</li> <li>• Call a poison control center or doctor for further treatment advice.</li> </ul>                                      |

**HOT LINE NUMBER**

Have the product container or label with you when calling a poison control center or doctor, or going for treatment. You may also contact 1-800-548-0469 for emergency medical treatment information.

**NOTE TO PHYSICIAN**

Contains petroleum distillates. Vomiting may cause aspiration pneumonia.

**ENVIRONMENTAL HAZARDS**

This material is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow drips and dust generated during paint removal to enter water. Dispose of paint cans in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, rivers, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) Permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent into sewer system without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

**PHYSICAL OR CHEMICAL HAZARDS: COMBUSTIBLE.** Do not use or store near heat or open flame. Use only with adequate ventilation during mixing, application and drying. Use absorbent clean-up material if spilled. For fire, bucket flames with foam, CO<sub>2</sub> or dry chemical. Wear MSHA/NIOSH certified breathing equipment.

**STORAGE AND DISPOSAL**

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. **Pesticide Storage:** Store in a closed, properly labeled container in a cool place. Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb and dispose of in accordance with local applicable regulations.

**Pesticide Disposal:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or insects is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance.

**Container Handling:** Non-refillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

**NOTICE! THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.** Made in U.S.A. P309 01-1014

PHX MAC #1399135 09/23/15 BLACK RED BLUE GOLD